



SANDRIFT Panels with *CLIMAPLUS* Superior Performance/  
DOWN DX/DXL Suspension System

**LEED Credits**

Recycled Content: 70% – 71%  
*CLIMAPLUS* Superior Performance for Mold/Mildew

MR				EQ		
Waste Reduction¹	Recycled Content	Regional Materials²	Rapidly Renewable Materials	Low-Emitting Materials	Daylight and Views	Acoustical Performance
●	●	●	●	●	●	●

**Features and Benefits**

- Uniquely textured cast product with durable surface that resists scrapes commonly caused by accessing the ceiling plenum.
- Integral color masks nicks and scratches.
- Optional FIRECODE™ formulation designed to meet life safety codes.
- *CLIMAPLUS* 30-year lifetime system warranty to withstand conditions up to 104 °F (40 °C)/95% relative humidity without visible sag when used with a DOWN® brand suspension system.

**Applications**

- Conference and lobby areas
- Department stores
- Entertainment and gaming
- Executive offices
- Restaurants


**Substrate**

- Cast mineral fiber




Fine-textured panel


Call 888.874.2450 for color samples




White




Parchment 103




Manila 246




Beige 142




Straw 143




Sandstone 090



Taupe 107




Charcoal 534




Flat Black 205


**Advantage Colors**




Silvertone 052




Breeze 2659




Blue Grey 564




Azure 2660




Slate 568




Spruce 567




Tuscany 2663




Sorbet 2658




Squash 2661




Safari 2662




Redwood 566




Sienna 565




Halo 206



Mist 053



Nectar 546



Quartz 082

30

Year System Warranty  
– No visible sag  
– Mold/mildew protection

SANDRIFT  
*CLIMAPlus*  
Panels

SANDRIFT  
Non-*CLIMAPlus*  
Panels

UL Classified

Edge	Panel Size	Class	Item No.	NRC	CAC Min.	LR <sup>3</sup>	Color <sup>4</sup>	Grid Options	VOC Emissions	Anti-Mold & Mildew	Abuse Resistant	Recycled Content <sup>5</sup>	Panel Cost
SL 	2'x2' x3/4" Paper-Back	Class A	808	.70 	38	.83	White Standard Advantage	A	Zero			71%	\$
FL 	2'x2' x3/4" Paper-Back	Class A	809	.70 	38	.83	White Standard Advantage	B, C, D	Zero			71%	\$
SL 	2'x2' x3/4" Foil-Back		815	.55	35	.83	White	A	Zero			70%	\$

Legend

Zero Emissions (VOC Class)

Classified as zero-emitting per standards established by the Collaborative for High-Performance Schools (CHPS), following California Specification 01350 testing methods.

CLIMAPlus Superior Performance<sup>6</sup>

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold/mildew.

**A**  
DONN<sup>®</sup>  
DX<sup>®</sup>/DXL<sup>™</sup>

**B**  
CENTRICITEE<sup>™</sup>  
DXT

**C**  
FINELINE<sup>®</sup>  
DXF

**D**  
FINELINE<sup>®</sup> 1/8  
DXFF

Grid Profile  
Options



Physical Data/  
Footnotes

**Product literature**  
Data sheet: SC1841

**ASTM E1264 classification**  
Type III, Form 4, Pattern Z

**ASTM E84 surface burning characteristics**  
Class A  
Flame spread: 25  
Smoke developed: 50

**Weight**  
1.65-1.70 lb./sq. ft. (Class A)  
Firecode weight

**Thermal resistance**  
R-1.7 (Class A)  
R-1.3 (Firecode)

**Maximum backloading**  
See Warranty for details.

**Maintenance**  
Can be cleaned easily with a soft brush or vacuum.

**Texture**  
The manufacturing process for cast ceiling panels creates natural, subtle texture variations, which is a distinguishing feature of these products. Because of potential variances between production dates, we recommend ordering and installing color cast products by production lot number.

**Footnotes**

1. Applies when USG acoustical ceilings recycling program is utilized.
2. Dependent on location; see Sustainability selector.
3. LR values are shown as averages.
4. To highlight the unique texture of SANDRIFT *CLIMAPlus* panels, choose light colors. See Colors selector for more information.
5. For details, see Sustainability selector.
6. Panel face and back surfaces treated with a patented, broad-spectrum antimicrobial standard formulation that inhibits and

retards the growth of mold/mildew. For details, see *Ceiling Systems Warranties and Limitations* (SC2102) and *CLIMAPlus Ceilings Certification of Performance* (SC2451).